



Notes:

- Type: Film to Glass
- Operating Voltage: $\leq 10\text{v}$
- Operation Temperature: $-20^\circ\text{C} \sim 65^\circ\text{C}$
Storage Temperature: $-30^\circ\text{C} \sim 70^\circ\text{C}$
- Life Time: 1,000,000 times
- Connect Material: FPC
- Response Time: $\leq 10\text{ms}$
- Linearity: $\leq 1.5\%$
- Transmittance: $\geq 75\%$
- Surface Hardness: $\geq 3\text{H}$ (pencil)
- Operation force: $60\text{g} \sim 150\text{g}$
- Resistance: X: $417\Omega \sim 1152\Omega$ Y: $155\Omega \sim 378\Omega$

TOLERANCES (UNLESS OTHERWISE STATED)		GreenTouch Technology Co.,Ltd			
DECIMALS	ANGLES $\pm 0.5^\circ$	GreenTouch		Ratio	18.9
$>2000\text{MM}$	$\pm 2.00\text{MM}$	Model No.:	GT-4W-18.5A-1	Unit	mm
$1600 < X \leq 2000\text{MM}$	$\pm 1.20\text{MM}$	Structure	G+F	Date	2015.8.5
$1200 < X \leq 1600\text{MM}$	$\pm 0.80\text{MM}$	Design	李俊	Date	2015.8.5
$800 < X \leq 1200\text{MM}$	$\pm 0.50\text{MM}$	Check	付作书	Date	2015.8.5
$400 < X \leq 800\text{MM}$	$\pm 0.40\text{MM}$	Release	汪琛	Date	2015.8.5
$120 < X \leq 400\text{MM}$	$\pm 0.30\text{MM}$			Page	1/1
$30 < X \leq 120\text{MM}$	$\pm 0.20\text{MM}$			Version	AD
$< 30\text{MM}$	$\pm 0.10\text{MM}$				