



- Notes:
- 1.Type: Film to Glasses
 - 2.Operating Voltage: ≤10V
 - 3.Operation Temperature: 20°C ~ 65°C
 - 4.Life Time: 1,000,000 times
 - 5.Storage Temperature: 30°C ~ 70°C
 - 6.Connect Material: FPC
 - 7.Response Time: ≤10ms
 - 8.Transmittance: ≥75%
 - 9.Surface Hardness: ≥3H (pencil)
 - 10.Operation force: 50g ~ 150g

11. Resistance: 500 < PIN1, PIN2 < 2500
 500 < PIN2, PIN3 < 2500
 500 < PIN4, PIN5 < 2500
 500 < PINS, PIN1 < 2500

TOLERANCES
(UNLESS OTHERWISE SPECIFIED)
 DECIMALS ANGLES 10.5%

>200MM	±2.00MM
100 - < 200MM	±1.20MM
50 - < 100MM	±0.80MM
20 - < 50MM	±0.50MM
< 20MM	±0.10MM

		GreenTouch Technology Co., Ltd	
Model No.:	GT-22H-228-1	Size:	22"
Structure:	GHF	Unit:	mm
Design:	张旭	Date:	2016.3.29
Check:	付作书	Date:	2016.3.29
Revision:	ESK	Date:	2016.3.29
Scale:	16:10	Scale:	1:1
Page:	1/1	Page:	1/1
Version:	AD	Version:	AD