


650CMH 65" LCD touch all-in-one PC

Greentouch's 650CMH 65" series conference machine adopts the perfect combination of the current Android operating system and the dual operating system of X86 hardware. It integrates many technologies such as high-definition display, human-computer interaction, multimedia information processing and network transmission, making it easy to write on the conference machine. Annotation, synchronous interaction, multimedia, remote video conferencing, etc., greatly improve communication efficiency in applications such as conferences, presentations, industry command, deployment, etc., and are the preferred solutions for office, teaching, and graphic interactive presentations in the information age.

Applications

- Education and training field
- Business unit
- Medical institutions
- Self-checking service



Features

- Optional touch technologies include: Greentouch capacitance;
- Built-in pluggable PC module
- Ultra-thin body
- Ultra-low standby power consumption
- One key switch
- Automatic switching of external video
- Worldwide agency approvals
- One year standard warranty

- "Designing for Touch" as the base
- Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—Green-Touch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System and ISO14001 Environmental Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ETL, ROHS and UL. The objective of GreenTouch is to become the most reliable supplier of touch screen, high value-added and special touch products and touch solutions in the world.

Specifications

Size	65"	
Model	GT-TC-650CMH	
Exterior	Shell material	Aluminum alloy frame, black
	Dimensions(mm)	1487.8×893×81.7MM
	Screen type	65" diagonal, 16:9, Active matrix TFT LCD
LCD	Useful screen area(mm)	1428(H)×803(V)
	Resolution	3840 x 2160 @ 60Hz
	Brightness (typical)	350cd/m2
	Contrast ratio	1400:1
	Colors	8 bit/16.7 Million
	Viewing angle (from center)	Horizontal (left/right): 89/89° or 178° in total; Vertical (up/down): 89/89° or 178° in total
Capacitance touch screen parameters	Touch type	Capacitive touch screen
	Touch points	10
	Touch drive mode	HID free drive
	Touch screen glass	4MM tempered glass
	Touch screen sensing method	Finger pad or capacitive pen
	Touch screen positioning resolution	4096X4096
	Touch system communication port	USB 2.0
	Detection function and calibration	With software automatic detection function
	Responding speed	<20ms
	Touch accuracy	±1mm
	Operating system	Support Win 7/8/10, Linux, android
	Service life	Theory unlimited
Anti-external light test	Full angle resistance to ambient light	
Computer host configuration	Motherboard	I5 4200U
	Main chipset	Haswell-U, Broadwell-U high-speed chipset
	CPU	Core series
	RAM	DDR, 8G
	Storage	SSD:128G
	Graphics card	Core display Intel® HD5500
	Network card	Integrated 10/100/1000M bps Ethernet
	USB 3.0	2
	USB 2.0	2
	EARPHONE	1
	MIC	1
	VGA output	1
HDMI	1	
WIFI	Scalable 2.4G/5G, 150/300Mbps	
Bluetooth	Scalable	
MIC	1	
Standard motherboard	Model	DZ-8386PVC1-C0TA-V5.1
	System version	Android 8.0
	Processor	MSD848(8386)
	Configuration	Memory 3G DDR3, storage 32G WIFI2.4GHz +5G (5G projection hotspot)
	Input port	RJ45*1 (side) HDMI*2 (side) TOUCH USB*1 (side) VGA*1 (side) VGA AUDIO IN*1 (side) YPBP*1 (side) AV*1 (side) TV*1 (side)
	Output port	SPDIF*1 (side) Earphone*1 (bottom)
	Audio	MPEG1/2 layer I/II, AC-3 (customization required), AAC-Lc, WMA
	Video	MPEG-2/4, AVS, H.264, H.265, TS, Realmedia
	Sound output power	10W+10W
	Number of speakers	2
Camera, microphone	None (optional external camera microphone module)	
Front interface	Front	USB 3.0 (PC USB) front, USB 2.0 (full channel shared USB) front
	Underside	HDMI IN bottom, TOUCH USB bottom, TYPE-C (USB 2.0 protocol) bottom
Power supply	Voltage range	AC 110~240V-50/60HZ
	Power consumption	About 200W
	Standby power consumption	≤0.5W
Surroundings	Operating temperature	-10° C - 55° C
	Working humidity	10% - 90%RH, No condensation
	Storage temperature	-20°C-60°C
	Storage humidity	10% - 90%RH, No condensation
Package	Package Size	1600x205x1002
	Net weight	37.2kg
	Gross weight	46kg

Ordering Information

Part Number	Display Ports	RAM	Storage	Surface Treatment	Availability
GT-TC-650CMH-I5-D8-S128	Intel Core i5	8G	128G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call: +86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.

2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.