1503A 15" LCD

Android touch all-in-one

GreenTouch's 3A series Android touch all-in-one PCs are touch solutions with low power consumption, ultra-thin body design, high-resolution display and excellent multi-touch interactive experience. Compared with ordinary monitors, 3A series of professional design and High performance is more suitable for applications in retail and other industries. Designed and built by GreenTouch, this model has a long life cycle and can supply long-term needs.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, it is recommended to choose the ultra-low power consumption and cost-effective ZC-3566 solution; for customers with high performance requirements, the optional performance is more Powerful ZC-83A solution, the board integrates multimedia decoding, LCD driver, Ethernet, HDMI, WIFI, 3G, Bluetooth, supports most of the current popular video and picture format decoding, supports HDMI video output, TF card and The SIM card holder with lock is more stable, which greatly simplifies the system design of the whole machine; built-in speaker, 12V low-voltage power supply.

The all-in-one comes with a range of output connections to support a variety of third-party peripherals. Standard ports include 2 standard USB ports, Gigabit wired network card interface and 1 3.5MM audio left and right channel output, 1 TF card and SIM card holder with lock, 1 HDMI video The output port is convenient for adding a second customer display.

The series features industry-leading GreenTouch projected capacitive touch technology. This model has global regulatory agency certification, as well as GreenTouch's warranty and after-sales service. It provides a cost-effective all-in-one touch solution for industrial embedded system integrators and value-added resellers (VARs).

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001Quality Management System and ISO14001 Environmental Management System. The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC, ETL, ROHS andUL. The objective of GreenTouch is to become the most reliable supplier oftouch screen, high value-added and special touch products and touch solutions in the world.

• "Design for simple and convenience" the idea

Outstanding quality, reliability and Cost-effective

Applications

- · retail terminal
- · Rail transit
- · Finance and other industries
- self service

Features

- Optional Motherboard Configuration inlcudes: ZC-3566 ZC-83A
- Touch technologies include:
 Projected Capacitor:
- Stylish appearance
- Continues to work even if the touchscreen is scratched
- · Easy integration, low

maintenance

- · Excellent performance
- Accuracy and reliabilityDrift free operation
- Worldwide agency approvals
- · One year standard warranty





Specifications

Case/ frame color	Black				
Machine dimensions	355.4mm(W) x279.41 mm(H),Thickness: 42.8mm				
Display type	15'Diagonal,Ratio4:3,Active matrix TFT LCD, LED backlight				
Resolution(pixel)	1024 x 768 @ 60Hz				
Active Area Dimensions	304.128mm(H) x 228.096mm(V)				
Display Colors	16.2M				
Brightness (Standard)	300 cd/m ²				
Response time (standard)	15ms				
View Angle(from center)	Horizontal (left / right): ±85° or a total of 170°				
	Vertical (up / down): ± 85° or a total of 170°				
Contrast ratio (standard)	1500: 1(Typ.)				
Touch Technology	projected capacitive Touch dip: wedd, eeti, iiitek Touch points; 1-10 Touch supply voltage: 5V Touch interface; USB				
	Touch support system; Windows, Android, linux				
Motherboard	ZC-3566 Rockchip RR3556 High-performance, low-power quad-core 64-bit Cortex-A55, the main frequency in the 18/002 ZC-838 ZC-838 Quanahi834, Cortex-A7 architecture, main frequency 1.2GHz				
Operating system	Android11/7.1				
Memory	DDR3 4GB/2GB/1GB				
Built in memory	EMMC FLASH 16G/32G (maximum expandable to 64G)				
Network support	3G、Ethernet, WiFi / Bluetooth 4.0, wireless peripheral extension				
Wireless	Built in WiFi or WiFi / BT module (optional), 802.11b/g/n, default single WiFi module, external 1 3dB omnidirectional antenna				
Speakers	Built-in 2°2W speakers				
HDMI Output					
USB interface	1, Support 1080P@120Hz,4kXZk@60Hz Output				
USB Interrace TF Card	2 xUSB HOST				
	Support TF Card				
Headset / Microphone	1 external headphone audio output				
Audio and video output	Support left and right channel output, built-in 8R / 2W power amplifier				
Video function	USB camera support				
Power	Extemal DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC Type: DC cartridge receptacle; Cartridge ID: 5.5 mm (± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartridge depth: 8.0 mm (± 0.3 mm);				
Power consumption (standard)	Depend on Motherboard and the minimum is 25W				
Temperature	Operating: 0°C to 60°C; Storage: -20°C to 60°C				
Humidity	Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)				
Warranty	1 year				
Weight (approx.)	Net weight: 3.5 kg(Typ.); Shipping: 5.0 kg (reference)				
Mounting options	100mm or 75mm VESA mounting				
Water and dust protection/Explosion-proof	IP65(front)/IK06(front)				
Surface treatment	AG AR AF (Optional)				
Agency Approvals	UL,cUL (Recognized), FCC, CE, CB,China RoHS CQC				

Ordering Information

		CPU	RAM	Storage		
1503A	GT-TC-1503A-RK3566-D4-S64	RK3566	4G	64G	Clear	Worldwide
	GT-TC-1503A-A83T-D1-S16	A83T	1G	16G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.