

GreenTouch's 3A series computer touch all-in-one computer, with low power consumption, ultra-thin body design, high-resolution display and excellent multi-touch interactive experience touch solutions, compared to ordinary monitors. 3A series of professional design and High performance is more suitable for applications in retail and other industries. Designed and built by GreenTouch, this model has a long life cycle and can supply long-term needs.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, the ultra-low power consumption and cost-effective INTEL 2177U solution is recommended; for customers with high performance requirements, the optional performance is more powerful. The core series I3/I5/I7-U solution, onboard Intel HD graphics and onboard audio decoding, optional memory size, built-in SSD solid state drive, can be used with a second 2.5-inch hard drive to increase storage capacity; dual-antenna WIFI, Built-in speaker, 12V low voltage power supply.

The All-in-One comes with a range of input/output connections to support a variety of third-party peripherals. Standard ports include 2 RS-232 serial port, 4 USB ports, Gigabit wired network card interface and 1 set of 3.5MM audio input ports and 1 set of audio output ports, 1 VGA and 1 HDMI video output port, which is convenient for adding Second officiant.

The series features industry-leading GreenTouch projected capacitive touch technology. This model has global regulatory agency certification, as well as GreenTouch's warranty and after-sales service. It provides a cost-effective all-in-one touch solution for industrial embedded system integrators and value-added resellers (VARs).

- "Design for simple and convenience" the idea
- Outstanding quality, reliability and Cost-effective

## About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product.Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO90010uality Management System . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation.Our products have been certified to CE, FCC, ROHS . The objective of GreenTouch is to become the most reliable supplier oftouch screen, high value-added and special touch products and touch solutions in the world.

### **Applications**

- retail terminal
- Rail transit · Finance and other industries
- self service

Features • Optional Motherboard Configuration inIcudes: Intel Bay Trail-d chipset with: Celeron 2117U@1.99GHz Intel Core-u series chipset with Intel Core 13-U Intel Core 17-U		Specifica Case/ fame color Mechine dimensions Display type Resolution(pixel) Active Area Dimensions Display Colors Bightness (Standard) Response time (Standard) View Angle(from center)
Touch technologies include: Projected Capacitor:     Stylish appearance     Continues to work even if the		Contrast ratio (standard) Touch Technology
touchscreen is scratched • Easy integration, low maintenance • Excellent performance	格本格达登 GreenTouch	Motherboard
<ul> <li>Accuracy and reliability</li> <li>Drift free operation</li> </ul>	Greenrouch	Graphics
Drift free operation		Sound Card
		RAM
<ul> <li>Worldwide agency approvals</li> </ul>		SSD
		HDD
<ul> <li>One year standard warranty</li> </ul>		Wifi
		Speakers
		Extra Video output
		USB interface
		Audio Interface
		RS232 interface
		Power
		Power consumption (standard)
	Transministra (	Supported OS
· · · · · · · · · · · · · · · · · · ·	se a la	Temperature
GreenTouc	n status se	Humidity
		Warranty
		Weight (approx.)
		Mounting options
		Water and dust protection/Explo
		Surface treatment

# cations

Case/ frame color	Black					
Machine dimensions	574.5mm(W) x346.8 mm(H),Thickness: 47mm					
Display type	23.6'Diagonal,Ratio16:9,Active matrix TFT LCD, LED backlight					
Resolution(pixel)	1920 x 1080 @ 60Hz					
Active Area Dimensions	521.28mm(H) x 293.22mm(V)					
Display Colors	16.7M					
Brightness (Standard)	300 cd/m <sup>2</sup>					
Response time (standard)	3.5ms					
View Angle(from center)	Horizontal (left / right): ±85° or a total of 170° Vertical (up / down): ± 80° or a total of 160°					
Contrast ratio (standard)	1000: 1(Typ.)					
Touch Technology	projected capacitive Touch ohip: welda, eeti, liitek Touch points; 1-10 Touch supply voltage: SV Touch interfare: USB Touch support ystem; Windows, Android, linux					
Motherboard	Intel Bay Tail-I chipse with: Intel Bay Tail-I chipse with: Intel Core 15-0 Intel Core 15-0 Intel Core 15-0 Intel Core 15-0 Intel Core 15-0					
Graphics	Onboard Intel HD graphics					
Sound Card	Onboard Realtek ALC662HD audio decoding					
RAM	Optional 2GB,4GB,8GB					
SSD	32G,64G,128G,256G					
HDD	NA					
Wifi	Built-in 802.11b / g / n wireless, external two 3DB omnidirectional antenna					
Speakers	Built-in 2*2W speakers					
Extra Video output	1*VGA;1*HDMI					
USB interface	4*USB TYPE-A					
Network card	1 road onboard Realtek 8111e Gigabit					
Audio Interface	1*3.5mm Audio input;1*3.5mm Audio output					
RS232 interface	2*RS232(standard)interfaces					
Power	Extemal DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC) - Ty DC cartidge receptacle; Cartifidge ID: 5.5 mm (± 0.3 mm); Needle DD: 2.0 mm (+0.0 -0.1 mm); Cartifidge depth: 8.0 mm (± 0.3 mm);					
Power consumption (standard)	Depend on Motherboard and the minimum is 25W					
Supported OS	Support Windows OS(suggest Windows7 up );Linux;Android x86					
Temperature	Operating: 0°C to 60°C; Storage: -20°C to60 °C					
Humidity	Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing)					
Warranty	1 year					
Weight (approx.)	Net weight: 4.0 kg(Typ.); Shipping: 5.5 kg (reference)					
Mounting options	100mm or 75mm VESA mounting					
Water and dust protection/Explosion-proof	IP65(front)/IK06(front)					
Surface treatment	AG AR AF (Optional)					
Agency Approvals	FCC, CE,CB, China RoHS CQC					

## **Ordering Information**

Model	Part Number	CPU	RAM	Storage	Surface Treatment	Availability
	GT-TC-2363A-J1900-D2-S64	Intel J1900	2G	64G	Clear	Worldwide
22624	GT-TC-2363A-I3-D2-S128	Intel Core i3	2G	128G	Clear	Worldwide
2363A	2363A GT-TC-2363A-15-D8-S256	Intel Core i5	8G	256G	Clear	Worldwide
GT-1	GT-TC-2363A-17-D8-S512	Intel Core i7	8G	512G	Clear	Worldwide

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

#### Service call:+86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved