



- Notes:**
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10v$
  3. Operation Temperature:  $-20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force:  $60g \sim 150g$
  11. Resistance: X:  $220\Omega$ - $536\Omega$  Y:  $333\Omega$ - $814\Omega$

TOLERANCES  
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	$\pm 0.5\%$
$> 2000MM$	$\pm 2.0MM$	$\pm 2.0MM$
$1600 < X \leq 2000MM$	$\pm 1.2MM$	$\pm 1.2MM$
$1200 < X \leq 1600MM$	$\pm 0.8MM$	$\pm 0.8MM$
$800 < X \leq 1200MM$	$\pm 0.4MM$	$\pm 0.4MM$
$400 < X \leq 800MM$	$\pm 0.3MM$	$\pm 0.3MM$
$120 < X \leq 400MM$	$\pm 0.2MM$	$\pm 0.2MM$
$30 < X \leq 120MM$	$\pm 0.1MM$	$\pm 0.1MM$

		GreenTouch Technology Co., Ltd	
Model No.:	GT-4W-17B-1	Size	17"
Structure	GT-C	Unit	mm
Design	李松	Date	2020.03.31
Check	付竹生	Date	2020.03.31
Released	张强	Date	2020.03.31
Ratio	4:3	Scale	1:1
Page	1/1	Version	A0