



- Notes:**
1. Type: Film to Glass
 2. Operating Voltage: $\leq 10V$
 3. Operation Temperature: $-20^{\circ}C \sim 65^{\circ}C$
Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: $\leq 10ms$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 75\%$
 9. Surface Hardness: $\geq 3H$ (pencil)
 10. Operation force: 60g \sim 150g
 11. Resistance: X: 220Ω - 536Ω Y: 333Ω - 814Ω

TOLERANCES (UNLESS OTHERWISE STATED) DECIMALS ANGLES ±0.5%		Model No.:		Size	Ratio
>2000MM	±2.00MM	GT-4W-19C-1	19"	4:3	
1600 < X ≤ 2000MM	±1.20MM	Structure	GT-C	mm	1:1
1200 < X ≤ 1600MM	±0.80MM	Design	李松	Date	2020.03.31
800 < X ≤ 1200MM	±0.50MM	Check	付竹生	Date	2020.03.31
400 < X ≤ 800MM	±0.40MM	Released	张强	Date	2020.03.31
120 < X ≤ 400MM	±0.20MM				
30 < X ≤ 120MM	±0.10MM				
<30MM	±0.05MM				

GreenTouch 绿触科技 GreenTouch Technology Co., Ltd