

1853A 18.5" LCD Touch all-in-one PC

GreenTouch's 3A series computer touch all-in-one computer, with low power consumption, ultra-thin body design, high-resolution display and excellent multi-touch interactive experience touch solutions, compared to ordinary monitors, 3A series of professional design and High performance is more suitable for applications in retail and other industries. Designed and built by GreenTouch, this model has a long life cycle and can supply long-term needs.

This model is versatile and powerful, with modular design and optional configuration. For customers with low performance requirements, the ultra-low power consumption and cost-effective INTEL J1900 solution is recommended; for customers with high performance requirements, the optional performance is more powerful. The core series I3/I5/I7-U solution, onboard Intel HD graphics and onboard audio decoding, optional memory size, built-in SSD solid state drive, can be used with a second 2.5-inch hard drive to increase storage capacity; dual-antenna WIFI, Built-in speaker, 12V low voltage power supply.

The All-in-One comes with a range of input/output connections to support a variety of third-party peripherals. Standard ports include 2 RS-232 serial port, 4 USB ports, Gigabit wired network card interface and 1 set of 3.5MM audio input ports and 1 set of audio output ports, 1 VGA and 1 HDMI video output port, which is convenient for adding Second officiant.

The series features industry-leading GreenTouch projected capacitive touch technology. This model has global regulatory agency certification, as well as GreenTouch's warranty and after-sales service. It provides a cost-effective all-in-one touch solution for industrial embedded system integrators and value-added resellers (VARs).

Features

- Optional Motherboard


Configuration includes:

- Intel Celeron J1900;
- Intel Core series
- Intel Core I3-U
- Intel Core I5-U
- Intel Core I7-U

- Touch technologies include:
Projected Capacitor:
- Stylish appearance
- Continues to work even if the touchscreen is scratched
- Easy integration, low maintenance
- Excellent performance
- Accuracy and reliability
- Drift free operation

- Worldwide agency approvals

- One year standard warranty



- “Design for simple and convenience” the idea
- Outstanding quality, reliability and Cost-effective

About GreenTouch

Shenzhen GreenTouch Technology Co., Ltd. is a professional manufacturer of product. Our company specializes in R&D, manufacture and marketing of high-grade touch screen and value-added touch machine. Our company has our own brand—GreenTouch and provides customers with touch products including SAW touch screen, IR touch screen, four-wire touch screen, five-wire touch screen, various touch screen monitors and touch all in one PC TV. GreenTouch has automatic production lines and the sealed dust-free workshops and has been certified to ISO9001 Quality Management System and . The products are inspected in strict accordance with the quality management system. Quality management becomes an essential part of operation. Our products have been certified to CE, FCC, ROHS . The objective of GreenTouch is to become the most reliable supplier of touch screen, high value-added and special touch products and touch solutions in the world.

Applications

- retail terminal
- Rail transit
- Finance and other industries
- self service

Specifications

| | |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Case/ frame color | Black |
| Machine dimensions | 456.9mm(W) x 277.4 mm(H), Thickness: 47 mm |
| Display type | 18.5" Diagonal, Ratio 16:9, Active matrix TFT LCD, LED backlight |
| Resolution(pixel) | 1366 x 768 @ 60Hz |
| Active Area Dimensions | 408.5mm(H) x 229mm(V) |
| Display Colors | 16.7M |
| Brightness (Standard) | 250 cd/m ² |
| Response time (standard) | 1.4ms |
| View Angle(from center) | Horizontal (left / right): ± 85° or a total of 170° Vertical (up / down): ± 80° or a total of 160° |
| Contrast ratio (standard) | 1000: 1(Typ.) |
| Touch Technology | projected capacitive Touch chip: weida Touch points: 1-10 Touch supply voltage: 5V Touch interface: USB Touch support system: Windows, Android, linux |
| Motherboard | Intel Core I34030U |
| Graphics | Onboard Intel HD graphics |
| Sound Card | Onboard Realtek ALC662HD audio decoding |
| RAM | 4GB |
| SSD | 128G |
| HDD | NA |
| Wifi | Built-in 802.11b / g / n wireless, external two 3DB omnidirectional antenna |
| Speakers | Built-in 2"2W speakers |
| Extra Video output | 1"VGA; 1"HDMI |
| USB interface | 4"USB TYPE-A |
| Network card | 1 road onboard Realtek 8111e Gigabit |
| Audio Interface | 1"3.5mm Audio input; 1"3.5mm Audio output |
| RS232 interface | 2"RS232(standard) interfaces |
| Power | External DC, input voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS (for all in one PC) - Type: DC cartridge receptacle; Cartridge ID: 5.5 mm (± 0.3 mm); Needle OD: 2.0 mm (+0.0 -0.1 mm); Cartridge depth: 8.0 mm (± 0.3 mm); |
| Power consumption (standard) | Depend on Motherboard and the minimum is 25W |
| Supported OS | Support Windows OS(suggest Windows7 up);Linux:Android x86 |
| Temperature | Operating: 0°C to 50°C; Storage: -20°C to 60°C |
| Humidity | Operating: 20% to 80% (non-condensing); Storage: 5% to 95% (non-condensing) |
| Warranty | 1 year |
| Weight (approx.) | Net weight: 4.4 kg(Typ.); Shipping: 6.2 kg (reference) |
| Mounting options | 100mm or 75mm VESA mounting |
| Water and dust protection/Explosion-proof | IP65(front)/IK06(front) |
| Surface treatment | NA |
| Agency Approvals | FCC, CE,CB, China RoHS CQC |

Ordering Information

| Model | CPU | RAM | Storage | Surface Treatment | Availability |
|------------------------------|---------------|-----|---------|-------------------|--------------|
| GT-TC3A-185-I34030U-D4GS128G | Intel Core i3 | 4G | 128G | Clear | Worldwide |

To find out more about our extensive range of GreenTouch touch solutions, go to www.greentouch.com.cn, or ifo@greentouch.com.cn

Service call: +86-755-29370883/29371519

Shenzhen GreenTouch Technology Co., Ltd. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. GreenTouch (logo) and Shenzhen GreenTouch Technology Co., Ltd. Copyright . All rights reserved.

2016 Shenzhen GreenTouch Technology Co., Ltd. All rights reserved.